


Tipo di attacchi disponibili Type of link



Modello Model	Tipo attacco Type of link	Potenza Power	Forza allo strappo Force		Portata olio Oil capacity	Peso minimo Minimum weight	Dimensioni Dimensions		
			Kg.	Kg.			A	B	C
GM 80	F	3.2	7800	650	30-70	12-20	1300	820	550
GM 80	E (12 ton)	3.2	7800	827	30-70	12-20	924	820	550
GM 100	F	5.5	16000	1100	70-200	14-30	1500	1050	650
GM 100	E (12 ton)	5.5	16000	1135	70-200	14-30	1024	1050	650
GM 125	F	7.2	22000	1650	70-200	22-45	1600	1250	700
GM 125	E (12 ton)	7.2	22000	1862	70-200	22-45	1074	1250	700

Le prestazioni ottimali si ottengono con la portata olio minima indicata
For optimum performances use the indicated minimum flow rate



Il peso dell'escavatore è indicativo, per abbinare la giusta attrezzatura, è necessario consultare il diagramma delle portate dell'escavatore.
Excavator weight is indicative. To choose the correct attachment consult also excavator lift capacities.

la pressione minima per il funzionamento è di: **(GM 80) BAR 80 - (GM 100) BAR 120 - (GM 125) BAR 140**
Minimum pressure for operation is: **(GM 80) BAR 80 - (GM 100) BAR 120 - (GM 125) BAR 140**

ACCESSORI - O PTIONS



Staffa basculante per escavatori dal peso (Solo con attacco "E")
Suspension for excavators weight (Only for link "E")

Ton. 12-25
Ton. 26-45



GJ 2800 dim.: 1890 x 1000 x h 300

