



Tipo di attacchi disponibili
Type of link



Modello Model	Tipo attacco Type of link	Denti (su richiesta) Teeth (on request)	Capacità	Peso	Portata	Pressione	Cilindri		Forza chiusura Closing force	Dimensioni Dimensions				
			Lt.	Kg.	Ton.	Max Bar	Ton.			KN. (Bar 320)	A	C	D	E
GOA 131	PE	3	130	138	0,20	320	1	0,3-0,8	39,5	1160	490	815	640	440
GOA 131 K (4,5 ton)	K	3	130	165	0,20	320	1	0,3-0,8	39,5	1160	740	815	890	440
GOA 151	PE	3	150	146	0,25	320	1	0,4-0,9	39,5	1160	490	815	640	540
GOA 151 K (4,5 ton)	K	3	150	183	0,25	320	1	0,4-0,9	39,5	1160	740	815	890	540
GOA 181	PE	5	180	156	0,30	320	1	0,5-0,9	39,5	1160	490	815	640	640
GOA 181 K (4,5 ton)	K	5	180	190	0,30	320	1	0,5-0,9	39,5	1160	740	815	890	640
GOA 201	PE	5	200	175	0,35	320	1	0,6-1,0	39,5	1160	490	815	640	740
GOA 201 K (4,5 ton)	K	5	200	190	0,35	320	1	0,6-1,0	39,5	1160	740	815	890	740
GOA 231	PE	5	230	171	0,40	320	1	0,8-1,5	39,5	1160	490	815	640	840
GOA 231 K (4,5 ton)	K	5	230	210	0,40	320	1	0,8-1,5	39,5	1160	740	815	890	840
GOA 321	PE	5	320	195	0,60	320	1	1,0-1,8	32,6	1290	575	1020	710	840
GOA 321 K (4,5 ton)	K	5	320	222	0,60	320	1	1,0-1,8	32,6	1290	760	1020	960	840
GOA 401	PE	5	400	201	0,70	320	1	1,2-2,0	32,6	1290	575	1020	710	1040
GOA 401 K (4,5 ton)	K	5	400	240	0,70	320	1	1,2-2,0	32,6	1290	760	1020	960	1040



La portata della gru si intende con il braccio tutto sfilato. Questo dato è puramente indicativo, per abbinare la giusta attrezzatura, è necessario consultare il diagramma delle portate della gru. Crane capacity refers to crane boom at its maximal extension. This data is indicative. To choose the correct attachment consult also crane lift capacities.

ACCESSORI - OPTIONS



Valvola di blocco
Check valve



Staffa basculante per gru da autocarri
Connecting link for truck crane



Kit dente
Tooth kit



Set paratie laterali smontabili
Removable side plates

GOA 131 - 231
GOA 321 - 401

