

TYPE:	T12-42-S	T12-45-S	T12-47-S	T12-49-S	T12-51-S	T12-53-S
X (mm)	800	900	1200	1200	1200	1200
L (mm)	4200	4500	4700	4900	5050	5300
O (mm)	220	220	220	220	220	220
K	52°	50°	53°	50°	47°	55°
R (mm)	2710	2750	2830	2830	2830	2990
T (mm)	130	130	130	130	130	130
Weight <sup>1</sup> (kg)	1725	1750	1800	1825	1850	1975
DS (mm)	945	975	995	995	995	990
Min./max. container length (mm)	3400-5300	3600-5600	3700-5800	3900-6000	4050-6150	4120-6400
C (mm)	200	200	200	200	200	200
Loading (time) <sup>2</sup> (s)	32	33	37	37	37	44
Unloading (time) <sup>2</sup> (s)	38	39	44	44	44	52
Tipping (time) <sup>2</sup> (s)	33	33	37	37	37	44
Fast unloading (time) <sup>2</sup> (s)	12	12	14	14	14	16
Pump (l/min)	47	47	47	47	47	47

H = Hook height, CH = Chassis height, DS = Lowest pick up point (depending on hook- and chassis height)

<sup>1</sup> Rough estimation based on a standard system, filled with oil and without mounting kit accessories.

<sup>2</sup> Rough estimation based on PTO type C, pump 40 l/min., motor 1200rpm, PTO transmission i = 1.0 and dependent on cylinder thickness.  
Pressure: 350 bar

