

TYPE:	T16-47-S	T16-49-S	T16-51-S	T16-53-S	T16-55-S	T16-57-S
X (mm)	1000	1000	1000	1200	1200	1200
L (mm)	4700	4900	5050	5300	5500	5700
O (mm)	220	220	220	220	220	220
K	54°	50°	48°	55°	52°	49°
R (mm)	2870	2870	2870	3030	3030	3030
T (mm)	130	130	130	130	130	130
Weight <sup>1</sup> (kg)	1850	1875	1900	2050	2075	2100
DS (mm)	1280	1280	1280	1130	1130	1130
Min./max. container length (mm)	3700-5800	3900-6000	4050-6150	4100-6400	4300-6600	4500-6800
C (mm)	200	200	200	200	200	200
Loading (time) <sup>2</sup> (s)	35	35	35	42	42	42
Unloading (time) <sup>2</sup> (s)	43	43	43	51	51	51
Tipping (time) <sup>2</sup> (s)	38	38	38	45	45	45
Fast unloading (time) <sup>2</sup> (s)	13	13	13	16	16	16
Pump (l/min)	64	64	64	64	64	64

H = Hook height, CH = Chassis height, DS = Lowest pick up point (depending on hook- and chassis height)

<sup>1</sup> Rough estimation based on a standard system, filled with oil and without mounting kit accessories.

<sup>2</sup> Rough estimation based on PTO type C, pump 60 l/min., motor 1200rpm, PTO transmission i = 1.0 and dependent on cylinder thickness.  
Pressure: 350 bar

