

TYPE:	T26-51-SK	T26-53-SK	T26-55-SK	T26-57-SK	T26-60-SK	T26-62-SK	T26-65-SK	T26-67-SK
X1 (mm)	800	1000	900	1000	1200	1200	1400	1400
X2 (mm)	+1150	+1150	+1150	+1150	+1150	+1150	+1150	+1150
L (mm)	5050	5300	5500	5700	5950	6200	6450	6650
O (mm)	250	250	280	280	280	280	280	280
K	53°	53°	54°	54°	54°	54°	51°	51°
R1 (mm)	2445	2445	2525	2600	2635	2820	2710	2860
R2 (mm)	3005	3005	3110	3210	3260	3505	3355	3555
R3 (mm)	3375	3375	3475	3560	3600	3815	3685	3860
T (mm)	130	130	130	130	130	130	130	130
Weight ¹ (kg)	2625	2675	3050	3100	3150	3200	3250	3325
DS (mm)	1055	1055	915	980	1010	1160	1070	1190
Min./max. container length (mm)	3150-6200	3150-6400	3450-6600	3550-6800	3600-7050	3850-7300	3900-7550	4100-7750
C (mm)	200	200	200	200	200	200	100	100
Loading (time) ² (s)	30	31	35	36	37	37	38	43
Unloading (time) ² (s)	38	39	45	45	46	46	46	51
Tipping (time) ² (s)	33	33	39	39	39	39	39	44
Fast unloading (time) ² (s)	12	12	14	14	14	14	14	16
Pump (l/min)	108	108	108	108	108	108	108	108

H = Hook height, CH = Chassis height, DS = Lowest pick up point (depending on hook- and chassis height)

¹ Rough estimation based on a standard system, filled with oil and without mounting kit accessories.

² Rough estimation based on PTO type C, pump 80 l/min., motor 1200rpm, PTO transmission i = 1.0 and dependent on cylinder thickness. Pressure: 350 bar

