

| TYPE:                                  | T26-49-S  | T26-51-S  | T26-53-S  | T26-55-S  | T26-57-S  | T26-60-S  | T26-62-S  | T26-65-S  | T26-67-S  |
|--|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| X (mm)                                 | 1000      | 1000      | 1200      | 1200      | 1200      | 1400      | 1400      | 1400      | 1500      |
| L (mm)                                 | 4900      | 5050      | 5300      | 5500      | 5700      | 5950      | 6200      | 6450      | 6650      |
| O (mm)                                 | 250       | 250       | 280       | 280       | 280       | 280       | 280       | 280       | 280       |
| K                                      | 49°       | 47°       | 54°       | 51°       | 48°       | 53°       | 50°       | 48°       | 48°       |
| R (mm)                                 | 2890      | 2890      | 3065      | 3065      | 3065      | 3185      | 3185      | 3265      | 3350      |
| T (mm)                                 | 130       | 130       | 130       | 130       | 130       | 130       | 130       | 130       | 130       |
| Weight <sup>1</sup> (kg)               | 2350      | 2400      | 2800      | 2825      | 2850      | 2900      | 2925      | 3050      | 3075      |
| DS (mm)                                | 1365      | 1365      | 1260      | 1260      | 1260      | 1150      | 1150      | 1210      | 1265      |
| Min./max. container length (mm)        | 3900-6000 | 4050-6150 | 4100-6400 | 4300-6600 | 4500-6800 | 4550-7050 | 4800-7300 | 5050-7550 | 5150-7750 |
| C (mm)                                 | 200       | 200       | 200       | 200       | 200       | 200       | 200       | 150       | 150       |
| Loading (time) <sup>2</sup> (s)        | 34        | 34        | 40        | 40        | 40        | 45        | 45        | 45        | 46        |
| Unloading (time) <sup>2</sup> (s)      | 41        | 41        | 48        | 48        | 48        | 54        | 54        | 54        | 55        |
| Tipping (time) <sup>2</sup> (s)        | 37        | 37        | 44        | 44        | 44        | 49        | 49        | 49        | 49        |
| Fast unloading (time) <sup>2</sup> (s) | 12        | 12        | 15        | 15        | 15        | 17        | 17        | 17        | 17        |
| Pump (l/min)                           | 108       | 108       | 108       | 108       | 108       | 108       | 108       | 108       | 108       |

H = Hook height, CH = Chassis height, DS = Lowest pick up point (depending on hook- and chassis height)

<sup>1</sup> Rough estimation based on a standard system, filled with oil and without mounting kit accessories.

<sup>2</sup> Rough estimation based on PTO type C, pump 80 l/min., motor 1200rpm, PTO transmission i = 1.0 and dependent on cylinder thickness.  
Pressure: 350 bar

